



### Main Features

- Native soft light
- Integrated power supply
- Size and weight comparable to S60-C
- SkyPanel S60-C front and mounting accessories compatible
- Digital twin
- Built-in wireless with Lumenradio CRMX and Bluetooth
- Remote maintenance via Claypaky's CloudIO
- Expanded wired connectivity options
- LiOS software with SkyPanel Classic on-board user interface
- Improved low-end dimming performance
- 4 individually controllable pixel zones
- RGBW LED light engine
- CCT range between 2,800 K - 10,000 K



# S60 Pro

Upgrade your workflow: faster, smarter, more efficient

The SkyPanel S60 Pro represents the perfect blend of the familiar and the new, combining the renowned benefits of the iconic S60-C with innovative updates that meet the demands of today's professionals.

### Seamless Integration

The S60 Pro fits effortlessly into your sets, studios, and rental inventories, with color consistency across all SkyPanel models and generations, plus full compatibility with S60-C optical accessories.

### Improved Workflow

Elevate your productions with enhanced dimming and light output, built-in wireless and PSU, new software features, and expanded connectivity.

### Advanced Virtual Tools


Embrace the future with our digital twin, enabling unmatched customization and control in pre-visualization and virtual production.

### Continuous Reliability

CloudIO ensures your S60 Pro stays updated and problem-free with dependable, easy remote maintenance.

### Photometric Data

Preliminary data.



### Set Configuration

Fixture	Color	Yoke	Cable
S60 Pro	<ul style="list-style-type: none"> <li>■ blue/silver</li> <li>■ black</li> </ul>	<ul style="list-style-type: none"> <li>Manual</li> <li>Pole Operated</li> </ul>	<ul style="list-style-type: none"> <li>Schuko Edison</li> <li>Chinese Japanese</li> <li>Australian Bare Ends</li> </ul>

## Specifications S60 Pro

Type of Lamphed	LED Soft Light
Optical System	Swappable Diffusion Panels
Light Aperture	approx. 645 x 300 mm / 25.4 x 11.8"
Beam Angle	103° (with Standard Diffusion)
Light Engine	RGBW LED Light Engine
White Light	2,800 K to 10,000 K Continuously Variable CCT with Full +/- Green
Color Modes	CCT, HSI, RGBW, Effects, xy, Gel, Source Matching
Pixel Zones	4
Color Rendition	CRI average >95 TLCI average >90 TM30Rf average >91
Camera Sensor Matching	Yes, via ARRI ALEXA Mode
Dimming	0 to 100 % Continuous High Resolution Low-end Dimming
Accessory Compatibility	All Classic SkyPanel S60-C front & mounting accessories

### Mechanical

Versions	Manual Pole Operated
Handling	Aluminum Yoke with High-Strength Tilt Lock Steel Yoke for Pole Operation (Pan, Tilt) Rail for Fixed and Center Mount Yokes
Mounting	28 mm spigot (Junior Pin)
Housing Colors	Blue/Silver, Black
Tilt Angle	+/- 90°
Weight with Manual Yoke	approx. 15 kg / 33.1 lbs (Internal PSU)

### Control Options



On-Board Control	On-Board Control Panel on Bottom of Fixture
Wired Control	DMX-512A, RDM, Art-Net 4, sACN, LAN (Web-control, ALSM, mDNS Bonjour, PTP, NTP) Data Continues to Pass While Fixture is Powered Off.
Built-In Wireless Control	CRMX Classic, CRMX2, W-DMX G3 / G4 / G4S / G5, BL, Native Bluetooth 5.0
Software Interface	LAN/EtherCon and USB-C
Digital Twin Available	Yes
CloudIO Remote Maintenance Tool	Yes
Software	LiOS

### Electrical (Lamphed)

Power Supply	Internal
Power Consumption	500 W Maximum
AC Voltage Range	110 - 240 V~, 50/60 Hz
AC Power Connection	In and Through, PowerCON® TRUE1 TOP Compatible
DC Voltage Range	48 to 52 V- (100% Output)
DC Power Connector	3-Pin XLR (Pin 1: Negative, Pin 2: Positive)
Protection Class / IP Rating	I / IP20
Ambient Temperature Operation	-20 to +45 °C / -4 to +113° F
Estimated LED Lifetime (L70)	40,000 Hours
Estimated Color Shift Over Lifetime (CCT)	+/- 5%
Certifications & Declarations of Conformity	CE, CB, ENEC, cNRTLus, FCC, PSE & more


### S60 Pro

Size: 698 x 348 x 135 mm / 27.5 x 13.7 x 5.3 in  
Weight: approx. 13 kg / 28.7 lbs




### S60 Pro MAN - with Manual Yoke

Size: 825 x 568 x 135 mm / 32.5 x 22.4 x 5.3 in  
Weight: approx. 15 kg / 33.1 lbs



### S60 Pro P.O. - with Pole Operated Yoke

Size: 796 x 569 x 135 mm / 31.3 x 22.4 x 5.3 in  
Weight: approx. 16,5 kg / 36.4 lbs



All specifications are nominal / typical values.  
Preliminary data.