

Power Beam

DAYLIGHT

18kW/12kW

FILMGEAR®




L18012DPB

LAMPHEAD CONTENTS

Lamp Housing with

- High Reflective Parabolic Glass Mirror
 - Inlet Cable with Multi-Pin Connector
 - Stirrup with Ø28mm Spigot
- # Exclude Lamp Bulb

PHOTOMETRIC DATA




		10m	25m	50m	75m	100m
18kW	Lux	724410	115905	28980	12885	7245
	Spot Beam Ø	0.96 m	0.96 m	0.96 m	0.96 m	0.96 m
18kW	Lux	63600	10170	2550	1125	645
	Flood Beam Ø	2.99 m	7.47 m	14.95 m	22.42 m	29.89 m
12kW	Lux	482940	77270	19320	8590	4830
	Spot Beam Ø	0.96 m	0.96 m	0.96 m	0.96 m	0.96 m
12kW	Lux	42400	6780	1700	750	430
	Flood Beam Ø	2.99 m	7.47 m	14.95 m	22.42 m	29.89 m


SPECIFICATIONS

Identity No.	L18012DPB
Capacity	18,000W / 12,000W
Lamp Bulb Voltage	200V / 160V
UV Protective Lens	Ø883mm
Lamp Type	HMI 18000W SE / HMI 12000W SE
Color Temp.	5600K
Lamp Holder	GX51 / GX38
Stirrup	Ø28mm (1-1/8 in.) Spigot
Class / IP Rating	1 / IP 23
Max. Surface Temp.	260 °C / 200 °C
Max. Ambient Temp.	45 °C
Min. Distance to Illuminated Object	15 m
Min. Distance to Flammable Object	2 m
Operating Range	+30° ~ 0° ~ -30°
Weight (lamphead)	92 kg


ACCESSORIES



Electronic Ballast
18kW/12kW



Head to Ballast Cable
(20m or 15m)



Transport Case

DIMENSIONS (mm)

