CONTROL SYSTEMS



KEY FEATURES

RDM, Artnet and sACN support
Factory and user presets for plug and play setups
Line Voltage or POE powered
1.8" OLED Display with rotary knob
99 Internal cues with fade and delay time
Remote configuration via internal webpage
Powder-coated aluminum ½ rack housing

SPECIFICATIONS

MOUNTING

Standalone

Truss-mount (M10 or M12 mounting hole) Wall-mount horizontal or vertical (included) DIN Rail horizontal or vertical (included) Rack-mount option (requires NET Shelf)

CONNECTIONS

Front

(4) 5pin DMX/RDM optically isolated ports
Ports are bidirectional for DMX In and Output
Full color OLED display
Encoder w. Push to Select / Exit Button

Back

Locking Power In/Thru
(2) Locking RJ45 Ethernet network connections (1x POE)

PHYSICAL

Length: 215 mm (8.5 in.) Width: 139 mm (5.5 in.) Height: 42 mm (1.65 in.) Weight: 1 kg (2.2 lbs)

APPROVALS/RATINGS

cETLus / CE / FCC / IP20

ELECTRICAL

100-240 V nominal, 50/60 Hz, 10W POE 802.3af



ORDERING

INCLUDED ITEMS

1.5m Seetronic power cable (EU or US version)

(2) Wallmount plates(2) DIN-Rail clamps

SKU

US #: NRE012

EU #: 1330000065

J Z U



