



Oververzadigde Roscopaint

VRAAG EEN OFFERTE AAN

WAAR TE KOPEN

Is een unieke vinyl acrylverf, verpakt in geconcentreerde vorm. Het is ontworpen om verdund te worden met water, tenminste 1: 1 en meer. Met zo'n enorme uitbreidbaarheid biedt Supersaturated het breedste scala van effecten die mogelijk zijn terwijl het uiterst economisch in gebruik is. Oververzadigd zorgt voor levendige, ondoorzichtige kleurvelden op veel verschillende oppervlakken. Het creëert ook heldere, doorschijnende wassingens waarbij de kleur qua intensiteit vergelijkbaar blijft met aniline kleurstoffen, zonder gezondheidsrisico's. Meervoudig verzadigde Roscopaint is geformuleerd met een uniek bindmiddel dat superieure adhesie, duurzaamheid en flexibiliteit geeft, zelfs op moeilijke oppervlakken zoals Rosco Projection Screens en Rosco Dance Floors. Het kan ook worden gebruikt als een tint in andere verven op waterbasis, bindmiddelen en coating.

Verkrijgbaar in 32 kleuren van kunstenaars die gemakkelijk kunnen worden vermengd of gecombineerd met andere Rosco Scenic Paints.

BESTEK

Afwerking: vlak / mat

Oplosmiddel: water

Bindmiddeltype: vinyl Acrylco polymeer

Verdunning: Verdun minimaal 1: 1 met water, Rosco Clear Acrylic Glaze of een combinatie van beide indien nodig. Verdunnen vermindert de kleurconcentratie en creëert "glazuur" -effecten. Verdunnen met meer dan 5 delen water kan de bindmiddelsterkte verminderen. Voeg toe in Rosco Clear Acrylic Glaze om de hechting en flexibiliteit te herstellen.

Surface Preparation: Surfaces should be clean, dry and free from dirt and grease. Prime porous surfaces, except fabrics, using Rosco Tough Prime. If painting a new plaster surface, prime wall with a commercial primer/sealer designed for raw plaster. Then use Rosco Tough prime as a final preparation.

Application: Stir contents well before each use. Apply by brush, roller, or spray gun. Apply in thin uniform coats, using a good quality brush or roller. Use overlapping strokes, keeping a wet edge. Change roller direction often to avoid patterns and streaking.

Film Thickness: 1:1 Dilution = 1.5 mil. Dry Film

Coverage: 3:1 Dilution = Approx. 300 sq. ft. per gallon (28 sq. m. per 3.79L), depending on substrate, application tool and film thickness.

Avg. Dry Time: At 75°F (24°C). Dries to the touch in 30-45 minutes. Can be recoated in 1-2 hours.

Clean-up: Soap and water.

Shelf Life: Minimum shelf life for unopened, sealed paint is approximately 24 months when stored in a temperature controlled location.

Packaging: 1 Quart Cans (0.946L). *Gallon and 5 gallons available (3.79L and 18.95L).

CAUTIONS: Do not apply when surface or air temperatures are below 50°F (10°C). Keep from freezing. Avoid prolonged contact with skin or breathing of spray. Do not take internally. Use adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**

All technical data, recommendations and service are accurate to the best of our knowledge. Rosco assumes no responsibility for the results obtained or damage incurred from use by the buyer in whole or in part since method of application and its use is beyond our control.

Product Numbers

150 05965 0032	Supersaturated Red - Quart
150 05968 0032	Supersaturated Green Shade Blue - Quart
150 05969 0032	Supersaturated Ultramarine Blue - Quart
150 05971 0032	Supersaturated Chrome Green - Quart
150 05972 0032	Supersaturated Emerald Green - Quart
150 05973 0032	Supersaturated Pthalo Green - Quart
150 05974 0032	Supersaturated Imperial Green - Quart
150 05975 0032	Supersaturated Magenta - Quart
150 05976 0032	Supersaturated Brilliant Red - Quart
150 05977 0032	Supersaturated Spectrum Red - Quart
150 05979 0032	Supersaturated Purple - Quart
150 05980 0032	Supersaturated Iron Red - Quart
150 05981 0032	Supersaturated Chrome Yellow - Quart
1500 5982 0032	Supersaturated Yellow Ochre - Quart
150 05983 0032	Supersaturated Raw Sienna - Quart
150 05984 0032	Supersaturated Moly Orange - Quart
150 05985 0032	Supersaturated Burnt Umber - Quart
150 05986 0032	Supersaturated Raw Umber - Quart

150 05987 0032	Supersaturated Burnt Sienna - Quart
150 05988 0032	Supersaturated Lemon Yellow - Quart
150 05989 0032	Supersaturated Turquoise Blue - Quart
150 05990 0032	Supersaturated Prussian Blue - Quart
150 05991 0032	Supersaturated Navy Blue - Quart
150 05992 0032	Supersaturated Paynes Grey - Quart
150 05993 0032	Supersaturated Leather Lake - Quart
150 05994 0032	Supersaturated Grass Green - Quart
150 05996 0032	Supersaturated Cerulean Blue - Quart
150 05997 0032	Supersaturated Hunter Green - Quart
150 05998 0032	Supersaturated Van Dyke Brown - Quart
150 06001 0128	Supersaturated Neutral* - Gallon
150 06002 0128	Supersaturated White* - Gallon
150 06002 0640	Supersaturated White* - 5 Gallon
150 06003 0032	Supersaturated Velour Black* - Quart
150 06003 0128	Supersaturated Velour Black* - Gallon
150 06003 0640	Supersaturated Velour Black* - 5 Gallon
150 05900 0KIT	Supersaturated Paint Test Kit