

## S-3822A/S

### 2-ch Simultaneous Battery Charger & Adaptor



S-3822A  
for Gold Mount



S-3822S  
for V-Mount

#### Features


- ◆ Portable battery charger
- ◆ 2-ch simultaneous charging
- ◆ 3A charging current per channel
- ◆ LED charging indicators
- ◆ Support AC to 4-pin XLR output

#### Specifications:

Input	100~240VA, 50/60Hz
Power	136W(Max)
Charging Output	DC 16.8V, 3A(Max)×2
Adapting Output	DC 15V, 6A(Max)
Working Temperature	0℃~+40℃
Working Humidity	10%~90%
Dimension	228mm×140mm×86mm(S-3822A) 228mm×140mm×120mm(S-3822S)
Weight	Appx 1.0kg



Can charge 2x **V-mount / Gold mount** batteries simultaneously. The charging output is DC **16.8V, 3Ax2**



LED indicates the charging status for each channel:  
**Red:** on charging, < 80%;  
**Yellow:** on charging, ≥80%;  
**Green:** charging finished.



AC-DC adapting output via 4-pin XLR female connector. Offer DC **15V, 6A, 90W** output. (will not output when battery is charging)



SWIT Electronics Co., Ltd.  
 Website: [www.swit.cc](http://www.swit.cc)  
 Email: [contact@swit.cc](mailto:contact@swit.cc)  
 Tel: +86 2585805753  
 Fax: +86 2585805296

Distributed by: