



VELVET LIGHT PRODUCTS SPECIFICATIONS

VELVET LIGHT 1

COLOUR TEMPERATURE	adjustable from 3000K a 6000K (100K increments)
LIGHT INTENSITY	dimnable 0 to 100 (smooth and flicker-free)
COLOR RENDERING INDEX	95 CRI
DIMENSIONS	370 x 308 x 68 mm (panel) 435 x 395 x 68 mm (panel + yoke)
WEIGHT	3,2 kgs (panel) 3,6 kgs (panel + yoke)
POWER DRAW	75 W
POWER SUPPLY	12 - 35 VDC Vlock or Gold battery mount plate 90-264 VAC 50/60Hz
BEAM ANGLE	100°
PHOTOMETRICS	1700 lux / 157 fc at 1m / 3 feet 210 lux / 19 fc at 3m / 10 feet
LED RATED LIFE	more than 50.000 hours L70 more than 35.000 hours L80
POWER CONNECTION	Neutrik XLR-3 in connector
DMX	DMX-RDM with XLR-5 in connector
OUTPUT FREQUENCY	20KHz flicker-free up to 3000fps
OPERATION TEMPERATURE	from -20°C to +40°C
COOLING	no-noise, fan-free passive cooling
PROTECTION	IP54 rainproof, indoor or outdoor use
VELVET LED TECHNOLOGY	OSRAM selected BIN LED core unit + optic diffuser + CPU software control
RIGGING OPTIONS	aluminum yoke with 16 female combined with 28 pin, quick link swivel ball head, multipanels yokes
QUICK MOUNTING ACCESSORIES	AC power supply, Vlock or Gold adapter, DMX 512 splitter cable in&out, foldable Snapgrid, removable barn doors, cordura case, hard case
CONSTRUCTION & FINISH	Black anodized extruded aluminum and black powder coated sheet aluminum



VELVET LIGHT 2

COLOUR TEMPERATURE	adjustable from 3000K a 6000K (100K increments)
LIGHT INTENSITY	dimnable 0 to 100 (smooth and flicker-free)
COLOR RENDERING INDEX	95 CRI
DIMENSIONS	670 x 308 x 68 mm (panel) 768 x 435 x 68 mm (panel + yoke)
WEIGHT	6 kgs (panel) 7 kgs (panel + yoke)
POWER DRAW	150 W
POWER SUPPLY	24 - 35 VDC double Vlock or Gold battery mount plate 90-264 VAC 50/60Hz
BEAM ANGLE	100°
PHOTOMETRICS	3600 lux / 334 fc at 1m / 3 feet 450 lux / 42 fc at 3m / 10 feet
LED RATED LIFE	more than 50.000 hours L70 more than 35.000 hours L80
POWER CONNECTION	Neutrik XLR-3 in connector
DMX	DMX-RDM with XLR-5 in connector
OUTPUT FREQUENCY	20KHz flicker-free up to 3000fps
OPERATION TEMPERATURE	from -20°C to +40°C
COOLING	no-noise, fan-free passive cooling
PROTECTION	IP54 rainproof, indoor or outdoor use
VELVET LED TECHNOLOGY	OSRAM selected BIN LED core unit + optic diffuser + CPU software control
RIGGING OPTIONS	aluminum yoke with 16 female combined with 28 pin, quick link swivel ball head, multipanels yokes
QUICK MOUNTING ACCESSORIES	AC power supply, double Vlock or Gold adapter, DMX 512 splitter cable in&out, foldable Snapgrid, removable barn doors, cordura case, hard case
CONSTRUCTION & FINISH	Black anodized extruded aluminum and black powder coated sheet aluminum