




**VELVET Light 1  
Rainproof**



**4LIGHT  
(AC & DC powered)**



**Litepanel  
1x1 Bi-color**



**Tecpro  
Felloni Bi-color HO**



**Fluorescent  
Divalite 400**



**Trucolor LS**

<b>Beam angle</b>	100°	30° to 75°	50°	50°	100°	160°
<b>Light class</b>	Soft light	Directional Key & Soft light	Soft light	Soft light	Soft light	Soft light
<b>Dimensions</b>	370 x 308 x 68 mm	337 x 207 x 70 mm	305 x 305 x 44 mm	304 x 304 x 76 mm	660 x 300 x 150	270 x 232 x 97
<b>Fixture weight</b>	3,2kg	2,4kg	1,4kg	2,5kg	6,4kg	2,3kg + 1,9kg PSU
<b>Power draw</b>	75W	100W	40W	24W	220W	167W
<b>Power Supply</b>	90-264 VAC 12-35 VDC	90-264 VAC 12-35 VDC	100-240VAC 14-28 VDC	100-240VAC 10-17 VDC	220 VAC	100-240 VAC
<b>Colour Temperature</b>	variable from 2700K to 6500K	variable from 2500K to 6500K	variable from 3200K to 5600K	variable from 3200K to 5600K	2 models: 3200K and 5600K	changing front diffuser 2700, 3200, 4300, 5600, 6500K
<b>Green / magenta correction</b>	No	1/8 and 1/4 plus and minusgreen	No	No	No	No
<b>Cooling</b>	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans	No	Passive, no fans
<b>Dimmer</b>	Yes	Yes	Yes	Yes	No	Yes
<b>Technology</b>	OSRAM selected BIN LED + optic diffuser + CPU control	Phillips high-power LED triplets + Fresnel + CPU	5mm LED	5mm LED	Fluorescent 4 tubes of 55W each	Remote Phosphor
<b>Lamp life</b>	more than 50.000 hours	more than 50.000 hours			5.000 hours	35.000 hours
<b>IP rating</b>	IP 54 rainproof	IP 21				
<b>PHOTOMETRICS</b>	<b>5600K</b>	<b>5600K at 40°</b>	<b>5600K</b>	<b>5600K</b>	<b>5600K at 100°</b>	<b>5600K 160°</b>
<b>1 meter</b>	1700 lux	7000 lux	1400 lux	1500 lux	2500 lux	
<b>3 meters</b>	210 lux	900 lux	170 lux	170 lux	310 lux	248 lux

Measurements made at an established temperature, with the light fixture at maximum intensity

October 2014

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending. Specifications subject to change without notice. 2014 © Copyright THELIGHT. All rights reserved



**VELVET Power 1  
SPOT Rainproof**



**VELVET Power 1  
FLOOD Rainproof**



**Litepanels Astra  
1x1**



**HMI 575W**



**Nila  
Boxer**



**Sumo Light 100  
Bi-color**

<b>Beam angle</b>	15° (tunable)	30° (tunable)	40°	7° to 50°	10° 25° 40° 60° 80°	30°
<b>Light class</b>	Long throw light	Long throw light	Hard light	Hard light	Hard light	Hard light
<b>Dimensions</b>	385 x 308 x 68 mm	385 x 308 x 68 mm	450 x 413 x 134 mm	272 x 250 x 315 mm	330 x 400 x 190	300 x 225 x 65
<b>Fixture weight</b>	4,5kg	4,5kg	3,2kg	8 kg + 5kg ballast	11kg	2kg
<b>Power draw</b>	100W	100W	110W	575W	200W	100W
<b>Power Supply</b>	90-264 VAC 12-35 VDC	90-264 VAC 12-35 VDC	100-240 VAC 13-24 VDC	220 VAC	90-305 VAC	100-230 VAC 12-48 VDC
<b>Colour Temperature</b>	variable from 2700K to 6500K	variable from 2700K to 6500K	variable from 3200K to 5600K	5600K	2 models: 3400K and 6000K	variable from 3000K to 5700K
<b>Green / magenta correction</b>	No	No	No	No	No	No
<b>Cooling</b>	Passive, no fans	Passive, no fans	Active with fans	Passive, no fans	Passive, no fans	Passive, no fans
<b>Dimmer</b>	Yes	Yes	Yes	No	Yes	Yes
<b>Technology</b>	high-power selected BIN LED + custom optics + CPU control	high-power selected BIN LED + custom optics + CPU control	high-power selected LED + custom optics	HMI lamp	Array of single colour LED	high-power selected LED + custom optics
<b>Lamp life</b>	more than 50.000 hours	more than 50.000 hours		500 hours	20.000 hours	
<b>IP rating</b>	IP 54 rainproof	IP 54 rainproof		IP 23	IP54	
<b>PHOTOMETRICS</b>	<b>5600K at 15°</b>	<b>5600K at 30°</b>	<b>5600K at 40°</b>	<b>5600K at 30°</b>	<b>5600K at 20°</b>	<b>5600K at 30°</b>
<b>1 meter</b>	42.000 lux	20.000 lux	8.600 lux			8.000 lux
<b>3 meters</b>	8.500 lux	2.700 lux	940 lux	7500 lux	3400 lux	1200 lux
<b>6 meters</b>	1.800 lux	750 lux		1900 lux	840 lux	

Measurements made at an established temperature, with the light fixture at maximum intensity

October 2014

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending  
Specifications subject to change without notice.  
2014 © Copyright THELIGHT. All rights reserved



**VELVET Light 2  
Rainproof**



**Kinoflo  
Celeb 200**



**Fluorescent 4  
tubes 120cms**



**Fluorescent  
Divalite 400**



**Bbs Area 48**



**Trucolor LS**

Beam angle	100°	100°	100°	100°	160°	160°
Light class	Soft light	Soft light	Soft light	Soft light	Soft light	Soft light
Dimensions	670 x 308 x 68 mm	610 x 350 x 130 mm	1320 x 330 x 90	660 x 300 x 150	356 x 275 x 115	270 x 232 x 97
Fixture weight	6kg	6,8kg	5,2kg	6,4kg	3,6kg	2,3kg + 1,9kg PSU
Power draw	150W	100W	300W	220W	150W	167W
Power Supply	90-264 VAC 24-35 VDC	100-240 VAC 18-28VDC	220 VAC	220 VAC	100-240VAC 12-20 VDC	100-240 VAC
Colour Temperature	variable from 2700K to 6500K	variable from 2700K to 5500K	2 models: 3200K and 5600K	2 models: 3200K and 5600K	changing front diffuser 2700, 3200, 4300, 5600, 6500K	changing front diffuser 2700, 3200, 4300, 5600, 6500K
Green / magenta correction	No	No	No	No	No	No
Cooling	Passive, no fans	Passive, no fans	Passive, no fans	No	Passive, no fans	Passive, no fans
Dimmer	Yes	Yes	No	No	Yes	Yes
Technology	OSRAM selected BIN LED + optic diffuser + CPU control	LED	Fluorescent 4 tubes of 75W each	Fluorescent 4 tubes of 55W each	Remote Phosphor	Remote Phosphor
Lamp life	more than 50.000 hours		5.000 hours	5.000 hours	50.000 hours	35.000 hours
IP rating	IP 54 rainproof					
<b>PHOTOMETRICS</b>	<b>5600K at 100°</b>	<b>5600K at 100°</b>	<b>5600K at 100°</b>	<b>5600K at 100°</b>	<b>5600K at 160°</b>	<b>5600K at 160°</b>
1 meter	3600 lux	1500 lux	2600 lux	2500 lux	4150 lux	
3 meters	450 lux	170 lux	360 lux	310 lux	380 lux	248 lux


Measurements made at an established temperature, with the light fixture at maximum intensity

October 2014

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending  
Specifications subject to change without notice.  
2014 © Copyright THELIGHT. All rights reserved

[www.thelight.com.es](http://www.thelight.com.es)



**VELVET Light 4**

**4LONG  
(AC & DC powered)**

**Kinoflo  
Celeb 400**

**Softlight 2000W**

**Fluorescent 4  
tubes 120cms**

**Trucolor  
HS**

Beam angle	100°	30° to 75°	100°	72°	100°	160°
Light class	Soft light	Directional Key & Soft light	Soft light	Soft light	Soft light	Soft light
Dimensions	1250 x 308 x 68 mm	620 x 207 x 70 mm	1115 x 360 x 130 mm	540 x 432 x 140	1320 x 330 x 90	532 x 290 x 97 mm
Fixture weight	11kg	4,4kg	12kg	7,5kg	5,2kg	5,5kg
Power draw	290W	147W	200W	2.000W	300W	400W
Power Supply	90-264 VAC 26-28 VDC	90-264 VAC 24-35 VDC	100-240 VAC 18-28 VDC	220 VAC	220 VAC	100-250 VAC
Colour Temperature	variable from 2700K to 6500K	variable from 2500K to 6500K	variable from 2700K to 5500K	3200K	2 models: 3200K and 5600K	changing front diffuser 2700, 3200, 4300, 5600, 6500K
Green / magenta correction	No	1/8 and 1/4 plus and minusgreen	No	No	No	No
Cooling	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans
Dimmer	Yes	Yes, local and DMX	Yes	No	No	Yes
Technology	OSRAM selected BIN LED + optic diffuser + CPU control	Phillips high-power LED triplets + Fresnel + CPU	LED	2 lamps of 1000W each	Fluorescent 4 tubes of 75W each	Remote phosphor
Lamp life	more than 50.000 hours	more than 50.000 hours		250 hours	5.000 hours	35.000 hours
IP rating	IP 51 dustproof	IP 21				
<b>PHOTOMETRICS</b>	<b>5600K at 100°</b>	<b>5600K at 40°</b>	<b>5600K at 100°</b>	<b>3200K at 72°</b>	<b>5600K at 100°</b>	<b>5600K at 160°</b>
1 meter	8000 lux	14.000 lux	3400 lux		2600 lux	
3 meters	1200 lux	1800 lux	440 lux	660 lux	360 lux	710 lux
6 meters	350 lux	500 lux		165 lux	300 lux	

Measurements made at an established temperature, with the light fixture at maximum intensity

October 2014

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending. Specifications subject to change without notice. 2014 © Copyright THELIGHT. All rights reserved.

[www.thelight.com.es](http://www.thelight.com.es)



**VELVET Light 2x2**



**Kinoflo Celeb 400Q**



**Mole 500W Softlite LED**



**Mole 900W Spacelight LED**



**Softlight 4000W**



**Spacelight 6000W**

Beam angle	100°	100°	170°		72°	
Light class	Soft light	Soft light	Soft light	Soft light	Soft light	Soft light
Dimensions	750 x 690 x 68 mm	760 x 660 x 130 mm	542 x 515 x 237 mm	920 x 1290 mm	540 x 432 x 140	850 x 915 mm
Fixture weight	12kg	11kg	8,2kg	14,5kg	17kg	18kg
Power draw	290W	200W	500W	900W	5.000W	6.000W
Power Supply	90-264 VAC 26-28 VDC	100-240 VAC 18-28 VDC	90-250 VAC	220 VAC	220 VAC	220V AC
Colour Temperature	variable from 2700K to 6500K	variable from 2700K to 5500K	2 models: 3200K and 5600K	2 models: 3200K and 5600K	3200K	3200K
Green / magenta correction	No	No	No	No	No	No
Cooling	Passive, no fans	Passive, no fans	Active with fans	Active with fans	Passive, no fans	Passive, no fans
Dimmer	Yes	Yes	Yes	Yes	No	No
Technology	OSRAM selected BIN LED + optic diffuser + CPU control	LED	LED	LED	Tungsten	Tungsten
Lamp life	more than 50.000 hours	more than 50.000 hours			250 hours	250 hours
IP rating	IP 51 dustproof		IP30	IP30		
<b>PHOTOMETRICS</b>	<b>5600K</b>	<b>5600K</b>	<b>5600K</b>	<b>5600K</b>	<b>3200K flood</b>	<b>3200K</b>
1 meter	8000 lux	3400 lux				
3 meters	1100 lux	440 lux	896 lux	300 Lux	3600 lux	700 lux
6 meters	300 lux				650 lux	170 lux

Measurements made at an established temperature, with the light fixture at maximum intensity

October 2014

[www.thelight.com.es](http://www.thelight.com.es)


THELIGHT technology is protected under Spanish license with international patents pending. Specifications subject to change without notice. 2014 © Copyright THELIGHT. All rights reserved.



**6LIGHT  
(AC & DC powered)**



**Kinoflo  
Celeb 200**



**Creamsource Mini  
Bender Flood**



**Redhead 800W**



**Fluorescent  
Parabeam 400**



**Nila  
Boxer**

<b>Beam angle</b>	30° to 125°	100°	44°	31° to 62°	100°	10° 25° 40° 60° 80°
<b>Light class</b>	Directional Key & Soft light	Soft light	Soft light	Hard light	Soft light	Hard light
<b>Dimensions</b>	337 x 302 x 70 mm	610 x 350 x 130 mm	438 x 392 x 100 mm	240 x 215 x 200 mm	620 x 610 x 205	330 x 400 x 190
<b>Fixture weight</b>	3,5kg	6,8kg	5,2kg	2,3 kg	10,9kg	11kg
<b>Power draw</b>	110W	100W	175W	800W	220W	200W
<b>Power Supply</b>	90-264 VAC 24-35 VDC	100-240 VAC 18-28 VDC	100-240 VAC 18-28 VDC	220 VAC	220 VAC	90-305 VAC
<b>Colour Temperature</b>	variable from 2500K to 6500K	variable from 2700K to 5500K	variable from 2700K to 6500K	3200K	2 models: 3200K and 5600K	2 models: 3400K and 6000K
<b>Green / magenta correction</b>	1/8 and 1/4 plus and minusgreen	No	No	No	No	No
<b>Cooling</b>	Passive, no fans	Passive, no fans	Active with fans	Passive, no fans	Passive, no fans	Passive, no fans
<b>Dimmer</b>	Yes, local and DMX	Yes	Yes	No	Yes	Yes
<b>Technology</b>	Phillips high-power LED triplets + Fresnel + CPU	LED	LED	Tungsten	Fluorescent 4 tubes of 55W each	Array of single colour LED
<b>Lamp life</b>	more than 50.000 hours			250 hours	5.000 hours	20.000 hours
<b>IP rating</b>	IP 21					IP 54
<b>PHOTOMETRICS</b>	<b>5600K at 40°</b>	<b>5600K at 100°</b>	<b>5600K at 44°</b>	<b>3200K at 62°</b>	<b>5600K at 100°</b>	<b>5600K at 40°</b>
<b>1 meter</b>	12500 lux	1500 lux	6300 lux		4900 lux	
<b>3 meters</b>	1500 lux	170 lux	860 lux	1300 lux	700 lux	1600 lux

Measurements made at an established temperature, with the light fixture at maximum intensity

October 2014

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending  
Specifications subject to change without notice.  
2014 © Copyright THELIGHT. All rights reserved

[www.thelight.com.es](http://www.thelight.com.es)





## THELIGHT 2014 COMPARISON CHART



**4LONG-STUDIO**



**Fresnel 650W**



**Fluorescent  
VistaBeam 600**



**Fluorescent  
Divalite 400**



**HMI 575W**



**ARRI L7-C**

<b>Beam angle</b>	30° to 75°	17° to 52°	100°	100°	7° to 50°	15° to 50°
<b>Light class</b>	Directional Key & Soft light	Hard light	Soft light	Soft light	Hard light	Hard light
<b>Dimensions</b>	622 x 205 x 148 mm	260 x 220 x 300	955 x 920 x 215	660 x 300 x 150	272 x 250 x 315 mm	384x 303 x 200mm
<b>Fixture weight</b>	7,6kg	4kg	21kg	6,4kg	8 kg + 5kg ballast	8,2 kg
<b>Power draw</b>	147W	650W	576W	220W 220 VAC	575W	160W
<b>Power Supply</b>	90-264 VAC	220 VAC	230 VAC	220 VAC	220 VAC	100-250 VAC
<b>Colour Temperature</b>	variable from 2500K to 6500K	3200K	2 models: 3200K and 5600K	2 models: 3200K and 5600K	5600K	variable from 2800K to 10000K
<b>Green / magenta correction</b>	1/8 and 1/4 plus and minusgreen	No	No	No	No	Yes
<b>Cooling</b>	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans	Active with fans
<b>Dimmer</b>	Yes, local and DMX	No	Yes	No	No	Yes
<b>Technology</b>	Phillips high-power LED triplets + Fresnel + CPU	Tungsten	Fluorescent 6 tubes of 96W each	Fluorescent 4 tubes of 55W each	HMI lamp	RGB+W LED
<b>Lamp life</b>	more than 50.000 hours	250 hours	5.000 hours	5.000 hours	500 hours	50.000 hours
<b>IP rating</b>	IP 21	IP 23			IP 23	IP 20
<b>PHOTOMETRICS</b>	<b>5600K at 40°</b>	<b>5600K at 52°</b>	<b>5600K at 100°</b>	<b>5600K at 100°</b>	<b>5600K at 50°</b>	<b>5600K at 50°</b>
<b>1 meter</b>	14.000 lux	12500 lux	1400 lux	2500 lux		6800 lux
<b>3 meters</b>	1800 lux	1200 lux		310 lux	3000 lux	750 lux
<b>6 meters</b>	500 lux	300 lux			800 lux	270 lux

Measurements made at an established temperature, with the light fixture at maximum intensity

**October 2014**

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending  
Specifications subject to change without notice.  
2014 © Copyright THELIGHT. All rights reserved

[www.thelight.com.es](http://www.thelight.com.es)



## THELIGHT 2014 COMPARISON CHART



**4x4LONG**



**HMI 1200W**



**Fluorescent 10 tubes**



**Softlight 2000W**



**Fluorescent VistaBeam 600**



**HMI 2500W**

<b>Beam angle</b>	40°	8° to 50°	100°	72°	100°	8° to 50°
<b>Light class</b>	Directional Key & Soft light	Hard light	Soft light	Soft light	Soft light	Hard light
<b>Dimensions</b>	900 x 750 x 100 mm	380 x 350 x 330 mm	1238 x 673 x 146	540 x 432 x 140	955 x 920 x 215	600 x 500 x 370 mm
<b>Fixture weight</b>	18,8kgs	12kg	22,3kg	7,5kg	21kg	15kg
<b>Power draw</b>	590W	1200W	750W	2.000W	576W	2.500W
<b>Power Supply</b>	90-264 VAC 24-35 VDC	220 VAC	220 VAC	220 VAC	230 VAC	100-240 VAC
<b>Colour Temperature</b>	variable from 2500K to 6500K	6000K	2 models: 3200K and 5600K	3200K	2 models: 3200K and 5600K	6000K
<b>Green / magenta correction</b>	1/8 and 1/4 plus and minusgreen	No	No	No	No	No
<b>Cooling</b>	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans	Passive, no fans
<b>Dimmer</b>	Yes	Yes	No	No	Yes	Yes
<b>Technology</b>	Phillips high-power LED triplets + Fresnel + CPU	HMI	Fluorescent 10 tubes of 75W each	2 lamps of 1000W each	Fluorescent 6 tubes of 96W each	HMI
<b>Lamp life</b>	more than 50.000 hours	500 hours	5.000 hours	250 hours	5.000 hours	500 hours
<b>IP rating</b>	IP 21	IP 23	IP 23	IP 20		IP 23
<b>PHOTOMETRICS</b>	<b>5600K at 40°</b>	<b>5600K at 50°</b>	<b>5600K at 100°</b>	<b>5600K at 72°</b>	<b>5600K at 100°</b>	<b>5600K at 50°</b>
<b>3 meters</b>	5800 lux		670 lux		1400 lux	
<b>6 meters</b>	1800 lux	1300 lux		660 lux		2900 lux
<b>9 meters</b>	1000 lux	800 lux		165 lux		1300 lux

Measurements made at an established temperature, with the light fixture at maximum intensity

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending  
Specifications subject to change without notice.  
2014 © Copyright THELIGHT. All rights reserved

October 2014

[www.thelight.com.es](http://www.thelight.com.es)