

## VELVET Light 2x2 COMPARISON CHART



**VELVET Light 2x2**



**Kinoflo  
Celeb 400Q**



**Mole 500W  
Softlite LED**



**Mole 900W  
Spacelight LED**



**Softlight 4000W**



**Spacelight  
6000W**

|                                   |   |                              |                           |                           |                    |                  |
|-----------------------------------|---|------------------------------|---------------------------|---------------------------|--------------------|------------------|
| <b>Beam angle</b>                 | 100°  | 100°                         | 170°                      |                           | 72°                |                  |
| <b>Light class</b>                | Soft light  | Soft light                   | Soft light                | Soft light                | Soft light         | Soft light       |
| <b>Dimensions</b>                 | 750 x 690 x 68 mm                                     | 760 x 660 x 130 mm           | 542 x 515 x 237 mm        | 920 x 1290 mm             | 540 x 432 x 140    | 850 x 915 mm     |
| <b>Fixture weight</b>             | 12kg  | 11kg                         | 8,2kg                     | 14,5kg                    | 17kg               | 18kg             |
| <b>Power draw</b>                 | 290W  | 200W                         | 500W                      | 900W                      | 5.000W             | 6.000W           |
| <b>Power Supply</b>               | 90-264 VAC<br>26-28 VDC                               | 100-240 VAC<br>18-28 VDC     | 90-250 VAC                | 220 VAC                   | 220 VAC            | 220V AC          |
| <b>Colour Temperature</b>         | variable from 2700K to 6500K                          | variable from 2700K to 5500K | 2 models: 3200K and 5600K | 2 models: 3200K and 5600K | 3200K              | 3200K            |
| <b>Green / magenta correction</b> | No  | No                           | No                        | No                        | No                 | No               |
| <b>Cooling</b>                    | Passive, no fans                                      | Passive, no fans             | Active with fans          | Active with fans          | Passive, no fans   | Passive, no fans |
| <b>Dimmer</b>                     | Yes   | Yes                          | Yes                       | Yes                       | No                 | No               |
| <b>Technology</b>                 | OSRAM selected BIN LED + optic diffuser + CPU control | LED                          | LED                       | LED                       | Tungsten           | Tungsten         |
| <b>Lamp life</b>                  | more than 50.000 hours                                | more than 50.000 hours       |                           |                           | 250 hours          | 250 hours        |
| <b>IP rating</b>                  | IP 51 dustproof                                       |                              | IP30                      | IP30                      |                    |                  |
| <b>PHOTOMETRICS</b>               | <b>5600K</b>  | <b>5600K</b>                 | <b>5600K</b>              | <b>5600K</b>              | <b>3200K flood</b> | <b>3200K</b>     |
| <b>1 meter</b>                    | 8000 lux  | 3400 lux                     |                           |                           |                    |                  |
| <b>3 meters</b>                   | 1100 lux  | 440 lux                      | 896 lux                   | 300 Lux                   | 3600 lux           | 700 lux          |
| <b>6 meters</b>                   | 300 lux   |                              |                           |                           | 650 lux            | 170 lux          |

Measurements made at an established temperature, with the light fixture at maximum intensity

October 2014

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending  
Specifications subject to change without notice.  
2014 © Copyright THELIGHT. All rights reserved



| Array of 6x fixtures | BASE LIGHT VELVET Light 2x2 |          | 3200K | 5600K |
|----------------------|-----------------------------|----------|-------|-------|
| Watts                | Model                       | Height   | Lux   | Lux   |
| 290                  | VELVET Light 2x2            | 3 meters | 1900  | 2200  |
| 290                  | VELVET Light 2x2            | 4 meters | 1200  | 1600  |
| 290                  | VELVET Light 2x2            | 5 meters | 900   | 1300  |
| 290                  | VELVET Light 2x2            | 6 meters | 800   | 1000  |



| Array of 6x fixtures | BASE LIGHT Spacelight 5Kw |          | 3200K | 5600K |
|----------------------|---------------------------|----------|-------|-------|
| Watts                | Model                     | Height   | Lux   | Lux   |
| 5000                 | Spacelight 5Kw            | 4 meters | 1200  |       |
| 5000                 | Spacelight 5Kw            | 5 meters | 900   |       |
| 5000                 | Spacelight 5Kw            | 6 meters | 750   |       |

Measurements made at an established temperature, with the light fixture at maximum intensity

[www.thelight.com.es](http://www.thelight.com.es)

THELIGHT technology is protected under Spanish license with international patents pending  
Specifications subject to change without notice.  
2014 © Copyright THELIGHT. All rights reserved

October 2014