COMPARISON WITH OTHER PANELS

- 2x times more light output
- best quality Osram LED
- super slim shock resistant aluminum body
- more than bi-colour 2700K to 6500K
- bi-directional DMX RDM
- modular design for multipanel
- affordable european made quality
- two years warranty. Made in Barcelona (Spain)

THELIGHT

www.thelight.com.es

info@thelight.com.es

Intellectual Property

THELIGHT VELVET light technology is protected under spanish patents and international patents pending

2015 © Copyright THELIGHT. All rights reserved.

the real power on soft LED light

VELVET 2x2 LIGHT

ROBUST

Rocky body 100% aluminum

SOFT LIGHT

Natural shadow-less light

POWERFUL

1100 Lux at 3m / 10 ft

THELIGHT

The unique aLL-in-one Light

VELVET 2x2 LIGHT

THE REAL POWER ON SOFT LED LIGHT

VELVET Light 2x2 is the most cost effective, simple to install and versatile to operate soft & space light available in the market.

Its big square surface produce more output than a tungsten spacelight 5.000W with only 290W without maintenance. The bi-color slim panel (7cms thick) doubles a 5.000W tungsten + light bank being much easier to install.

ADVANTAGES

- More than bi-color 2700K to 6500K
- Affordable European quality
- Silent fan-free operation
- Real power 1100 Lux at 3 meters
- Super slim (68mm) easy to rig
- Worldwide AC & DC powered
- Modular design for multipanel
- Flicker free up to 3000 fps
- Best quality Osram LED
- 2 years warranty. 100% made in Barcelona

MADE TO LAST

100% aluminium body

Robust dustproof IP51 body made to endure endure the tougher working conditions on on any location or studio

Best quality OSRAM LED

THELIGHT electronics and heatsink keep the LED in the optimum temperature to last beyond 50.000 hours

100% SILENT FAN-FREE OPERATION

THELIGHT state of the art passive cooling technology keep LED in their optimum temperature to beyond 50.000 hours.

MORE THAN BI-COLOR

VELVET is more than tungsten & daylight in the same unit: you can precisely adjust **color temperature from 2700 to 6500K**.

NATURAL SOFT LIGHT

Incredibly soft and wraparound quality light to easily get beauty shots and natural ambient

ADVANCED DMX RDM

Master-slave function: link several units to operate without console. The Master will control the other units

Bi-directional DMX-RDM: perfect solution on studio simplifying the asignment and channel addressing

QUALITY WHITE LIGHT

CRI >90 to get perfect skin tones and real colors

Absolutely consistent lamp to lamp to mix as many units as you wish and get exactly the same light quality and color reproduction

VELVET LIGHT 2x2 includes:

- on-board and DMX RDM digital control over:
  - Color temperature 2700K to 6500K
  - smooth Flicker-free dimming 0 to 100
- input DC power 26-28VDC
- detachable power supply 90-264VAC
- XLR-5 in&out connectors for remote DMX control
- yoke mount with 28 mm pin
- two years warranty

TECHNICAL SPECIFICATIONS

VELVET Light 2x2

COLOR TEMPERATURE	adjustable from 2700K to 6500K
LIGHT INTENSITY	dimmable 0 to 100 (smooth and flicker-free)
DIMENSIONS	670 x 620 x 68mm panel / 690 x 750 x 125mm panel + yoke + PSU
WEIGHT	12 Kg panel / 14 Kg panel + yoke + PSU
POWER DRAW	290 W
POWER SUPPLY	26-28V DC 90-264V AC 50/60Hz
PHOTOMETRICS	8.000 Lux / 740 fc at 1m / 3 feet 1.100 Lux / 102 fc at 3m / 10 feet 300 Lux / 28 fc at 6m / 20 feet
BEAM ANGLE	100°
LED RATED LIFE	more than 50.000 hours
COOLING	no noise, fan-free passive cooling
PROTECTION & CONSTRUCTION	dustproof IP51 rated, made of black anodized extruded aluminum and black powder coated sheet aluminum
VELVET LED TECHNOLOGY	OSRAM selected BIN LED + optic diffuser + CPU software control
QUICK MOUNTING ACCESSORIES	foldable Snapgrid 40° and 20°, yoke mount, AC power supply pole-op and multipanel yokes, power supply extension cable,removable barn doors, flight case

THELIGHT©

Specifications subjects to change without notice